

# HMS - DATBLAD

Versjon: 1.0

## SEKSJON 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** Mega Fusion - Off White  
**Other Names** Waterbased Primer, Product Code ABC  
**Recommended Use** Waterborne touch up primer

**Company Name** MagicEzy PTY Limited  
**Address** PO Box 5083, Maroochydore, QLD 4558  
Australia

**Emergency Tel** +6175456 4110 Available Monday – Friday, 8:00 a.m. – 5:00 p.m.  
**Phone** USA Poisons Centre 1-800 222 1222  
Australian National Poison Centre : 131-126

**Fax**

## SEKSJON 2. HAZARDS IDENTIFICATION

**Hazard Classification** Classified as Non Hazardous according to the criteria of NOHSC..

**Risk Phrases** R20/21/22 Harmful by inhalation, in contact with the skin and if swallowed.  
R36/38 Irritating to eyes and skin.  
R41 Risk of serious damage to the eyes

**Safety Phrases** S24/25 Avoid contact with skin and eyes.  
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

## SEKSJON 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion % (W/W)
	Water	7732-18-5	30-60
	Urethane resin	Not known	10-30
	Zinc Phosphate	7779-90-0	< 10
	Ammonium hydroxide	1336-21-6	< 1
	Mixed fungicide	Various	< 1
	Proprietary items	Various	Balance

---

**SEKSJON 4. FIRST AID MEASURES**

---

<b>Swallowed</b>	Rinse mouth. DO NOT induce vomiting. Never give anything by mouth to an unconscious person. <b>Seek medical attention immediately.</b>
<b>Eye</b>	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. <b>Seek medical attention without delay.</b>
<b>Skin</b>	Remove all contaminated clothing and wash before re-use. Wash affected area thoroughly with soap and water. If skin irritation or rash occurs get medical advice or attention.
<b>Inhaled</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
<b>Aggravated medical conditions caused by exposure.</b>	Can be irritating to skin with repeated or prolonged contact.
<b>Chronic Health Effects</b>	None anticipated with this product.

---

**SEKSJON 5. FIRE FIGHTING MEASURES**

---

<b>Extinguisher</b>	Foam. Dry chemical powder. Carbon dioxide.
<b>Hazards from combustion products</b>	Oxides of Carbon and Nitrogen.
<b>Special protective precautions and equipment for fire fighters</b>	Material can splatter above 100°C. Polymer film can burn. Do not allow contaminants and water from fire fighting to enter drains or water course.
<b>Hazchem code</b>	Not assigned

---

**SEKSJON 6. ACCIDENTAL RELEASE MEASURES**

---

<b>Emergency procedures</b>	In confined areas wear protective equipment. Keep spectators away and avoid breathing dust or vapours. Floor may be slippery, use care to avoid falling.
<b>Methods and materials for containment and clean up.</b>	<b>Minor spills</b> Contain and absorb small quantities with vermiculate or other absorbent material. Clean up spills immediately. Collect residues in a waste container.



**Annet** Beskyttelsesdrakt.  
Øyevask.

**Respirator** I et godt ventilert område og sprøytebokser som opprettholder dampnivåer under de anbefalte standardene, det er ikke nødvendig med åndedrettsvern. I begrensede rom, eller områder med begrenset ventilasjon der noen eksponeringsstandard kan overskrides, bruk egnet åndedrettsvern. AS / NZS 1716.

---

## SEKSJON 9. FYSISKE OG KJEMISKE EGENSKAPER

---

<b>Utseende</b>	Hvit farget væske
<b>Lukt</b>	Mild amin lukt
<b>pH</b>	7-10
<b>Damptrykk</b>	N/A
<b>Damptetthet</b>	N/A
<b>Kokepunkt</b>	100 °C
<b>Smeltepunkt</b>	0°C
<b>Løselighet</b>	Kan fortynnes med vann
<b>Tetthet</b>	1.120 Kg/L
<b>Prosent volatil av Vol</b>	< 50

---

## SEKSJON 10. STABILITET OG REAKTIVITET

---

<b>Kjemisk stabilitet</b>	Produktet anses å være stabilt under normale lagrings- og håndteringsforhold.
<b>Forhold som skal unngås</b>	Frysing, overdreven varme, raske temperaturendringer og inkompatible materialer.
<b>Inkompatible materialer</b>	Sterke oksidasjonsmidler, syrer og alkalier.
<b>Farlige nedbrytningsprodukter</b>	Oksyder av karbon og nitrogen og røyk.
<b>Farlige reaksjoner</b>	Farlig polymerisering vil ikke forekomme.

---

## SEKSJON 11. TOKSIKOLOGISK INFORMASJON

---

Ingen data tilgjengelig for dette produktet. Se enkelte råvarer.

### **Polyamidharpiks**

Oral LD<sub>50</sub> (rat):> 5,000 mg/

Kg. Fare for alvorlig øyeskade

---

## **SEKSJON 12. OPPLYSNINGER OM MILJØFARE**

---

Ingen data tilgjengelig for dette produktet.

Dette produktet må ikke komme inn i avløp eller vannbaner.

### **Polyamidharpiks**

Biologisk nedbrytbarhet Ikke lett biologisk nedbrytbar.

Unngå undergrunnsinntrengning.

Forhindre at produktet kommer i avløp.

Ikke forurens overflaten.

---

## **SEKSJON 13. FJERNING AV RESTER OG AVFALL**

---

**Avfallsbehandlingsmetoder og beholdere.** Ta kontakt med Statens Landbruksavfall for avhending.

**Spesielle forholdsregler for deponering eller forbrenning.** Forbrenne rester på et godkjent sted.  
Gjenvinn beholdere om mulig, eller kast dem i en godkjent deponi.

---

## **SEKSJON 14. OPPLYSNINGER OM TRANSPORT**

---

UN nummer Not specified

**UN fraktnavn** Ikke spesifisert  
**Klasse** Vannbasert filler. Ufarlig. Ikke begrenset  
**Risiko** Ingen

**Forpakn.gruppe Spesielle forholdsregler for brukeren** N.O.S.  
Bruken av en mengde materiale i et uventilert eller begrenset rom kan resultere i økt eksponering eller utvikling av en irriterende atmosfære. Før du begynner å vurdere bruk av mekanisk ventilasjon for å kontrollere eksponering.

**Hazchem kode** Ikke spesifisert.

---

## SEKSJON 15. OPPLYSNINGER OM LOVER OG FORSKRIFTER

---

Ikke tøm i avløp.  
Hold deg unna mat og drikke.

---

## SEKSJON 16. ANDR OPPLYSNINGER

---

**Dato for forberedelse:** 5. Desember 2014

**Dato for gjennomgang:** N/A

### Litteratur referanser

HMS-datablad for individuelle råvarer.

[www.toxnet.nlm.gov/cgi-bin/sis/htmlgen/TOXLINE](http://www.toxnet.nlm.gov/cgi-bin/sis/htmlgen/TOXLINE)

### Forkortelser:

NOHSC	National Occupational Health and Safety Commission
TWA	Time weighted average
STEL	Short term exposure limit
CAS Number	Chemical Abstract Service registry number
TLV	Threshold limit value

*Sikkerhetsdatablad oppdateres ofte. Pass på at du har en gjeldende kopi.*

**SLUTT**